

## PLUG OPERATED FRAC PORT

### APPLICATION

Plug Operated Frac Port is designed to provide an access for the process fluid to the isolation zone during hydraulic fracturing using a soluble key-plug.

- Uncemented casing / liner applications.
- Vertical, directional and horizontal wells.

### FEATURES AND BENEFITS

- Adjustable shear pressure prior to RIH.
- Mill out is not required.
- Full-bore ID.
- Activation of the sleeve is carried out by applying pressure after pumping the soluble key-plug.
- Locking mechanism holds the sleeve in the open/closed position.
- After fracturing the sleeve can be opened/closed using a special mechanical shifting tool.
- Frac port withstands high tensile loads and high differential pressures.
- Up to 6 fracturing stages with the toe sleeve as a part of the assembly.

### SUPPLY PACKAGE

- Plug Operated Frac Port.
- Key-Plug.

### TECHNICAL DATASHEET

TECHNICAL CHARACTERISTICS	VALUE
<b>Liner size, in</b>	<b>4.500</b>
Max OD, in	5.236
Min ID, in	3.858
Length, ft	3.1
Tensile, kip	202
Burst, psi	10,000
Collapse, psi	10,000
Material*	P-110
Max working temperature, °F	248

\* Other options are available as per Customer request.



PLUG  
OPERATED  
FRAC PORT